

**PRODUCT NAME: OXYGEN IN ARGON (1 PPM TO 50%)****1. Chemical Product and Company Identification****INDIANA  
OXYGEN***AS PACKAGED  
AND DISTRIBUTED  
BY***INDIANA OXYGEN COMPANY  
6099 WEST CORPORATE WAY  
INDIANAPOLIS, INDIANA 46278  
PHONE 1-317-290-0003****Emergency Contact: Infotrak  
1-800-535-5053****PRODUCT NAME:** OXYGEN IN ARGON (1 PPM TO 50%)**CHEMICAL NAME:** Oxygen in Argon**COMMON NAMES/SYNONYMS:** Oxygen in Argon Gas Mixtures**TDG (Canada) CLASSIFICATION:** 2.2**WHMIS CLASSIFICATION:** A, C (O<sub>2</sub> > 23.5%)**PREPARED BY:** Loss Control (908)464-8100/(905)501-1700**PREPARATION DATE:** 6/1/95**REVIEW DATES:** 3/22/00**2. Composition, Information on Ingredients****EXPOSURE LIMITS<sup>1</sup>:**

INGREDIENT	% VOLUME	PEL-OSHA <sup>2</sup>	TLV-ACGIH <sup>3</sup>	LD <sub>50</sub> or LC <sub>50</sub> Route/Species
Argon FORMULA: Ar CAS: 7440-37-1 RTECS #: CF2300000	50.0-99.9999	None Established	Simple Asphyxiant	Not Available
Oxygen FORMULA: O <sub>2</sub> CAS: 7782-44-7 RTECS #: RS2060000	0.0001-50.0	None Established	None Established	Not Available

<sup>1</sup> As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993)<sup>2</sup> Refer to individual state of provincial regulations, as applicable, for limits which may be more stringent than those listed here.<sup>3</sup> As stated in the ACGIH 1998-1999 Threshold Limit Values for Chemical Substances and Physical Agents.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

**3. Hazards Identification****EMERGENCY OVERVIEW**

Odorless colorless nonflammable gas. Mixtures which contain &gt; 23.5% oxygen act as oxidizers – will accelerate combustion and increase the risk of fire and explosion in combustible or flammable materials. Mixtures with less than 19.5% oxygen act as a simple asphyxiants. Effects may include headaches, dizziness and loss of consciousness. Non-toxic. Prolonged inhalation of high concentrations may cause coughing and lung effects. Contents under pressure. Use and store below 125 °F.

**PRODUCT NAME: OXYGEN IN ARGON (1 PPM TO 50%)**

**ROUTE OF ENTRY:**

Skin Contact No	Skin Absorption No	Eye Contact No	Inhalation Yes	Ingestion No
--------------------	-----------------------	-------------------	-------------------	-----------------

**HEALTH EFFECTS:**

Exposure Limits No	Irritant No	Sensitization No
Teratogen No	Reproductive Hazard No	Mutagen No
Synergistic Effects Other agents that effect the respiratory system		

Carcinogenicity: -- NTP: No IARC: No OSHA: No

**EYE EFFECTS:**

None expected.

**SKIN EFFECTS:**

None known or expected.

**INGESTION EFFECTS:**

None known or expected.

**INHALATION EFFECTS:**

Products which contain < 19.5% oxygen may act as simple asphyxiants. Effects of exposure to high concentrations of argon which displace the oxygen content in the air necessary for life are headaches, dizziness, labored breathing and eventual unconsciousness. Maintain oxygen levels between 19.5% and 23.5%.

Other effects of oxygen deficiency resulting from simple asphyxiants may include: rapid breathing, diminished mental alertness, impaired muscular coordination, faulty judgement, depression of all sensations, emotional instability, and fatigue. As asphyxiation progresses, nausea, vomiting, prostration, and loss of consciousness may result, eventually leading to convulsions, coma, and death.

Oxygen is non-toxic. Prolonged inhalation of high oxygen concentrations (> 75%) may affect coordination, attention, and cause tiredness or respiratory irritation.

Oxygen is more toxic when inhaled at elevated pressures. Depending upon pressure and duration of exposure, pure oxygen at elevated pressures (i.e.: divers) may cause cramps, dizziness, difficulty breathing, convulsions, edema, and death.

Elevated oxygen concentrations in incubators has caused visual impairment and blindness in premature infants. High oxygen concentrations primarily affect eyes which are not fully developed (see Section 11).

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** None known.

**PRODUCT NAME: OXYGEN IN ARGON (1 PPM TO 50%)**

**NFPA HAZARD CODES**

Health: 0  
Flammability: 0  
Instability: 0  
OXIDIZER (O<sub>2</sub> > 23.5%)

**HMIS HAZARD CODES**

Health: 0  
Flammability: 0  
Reactivity: 0

**RATINGS SYSTEM**

0 = No Hazard  
1 = Slight Hazard  
2 = Moderate Hazard  
3 = Serious Hazard  
4 = Severe Hazard

#### 4. First Aid Measures

**EYES:**

None required.

**SKIN:**

Not required.

**INGESTION:**

Not expected.

**INHALATION:**

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. Victims should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. If breathing has stopped administer artificial resuscitation and supplemental oxygen. Further treatment should be symptomatic and supportive.

#### 5. Fire Fighting Measures

Conditions of Flammability: Not flammable		
Flash point: None	Method: Not Applicable	Autoignition Temperature: None
LEL(%): None	UEL(%): None	
Hazardous combustion products: None		
Sensitivity to mechanical shock: None		
Sensitivity to static discharge: None		

**FIRE AND EXPLOSION HAZARDS:**

Mixtures which contain > 23.5% oxygen will accelerate fire and will support or initiate combustion/ explosion or organic matter and other oxidizable material. Cylinder may rupture violently from pressure when involved in a fire situation.

**EXTINGUISHING MEDIA:**

Nonflammable. Use any media suitable for surrounding fire. Use water spray to cool fire exposed containers.

**FIRE FIGHTING INSTRUCTIONS:**

For mixtures which contain > 23.5% oxygen, stop the flow of gas supporting fire. Firefighters should wear respiratory protection (SCBA) and full turnout or Bunker gear. Continue to cool fire-exposed cylinders until well after flames are extinguished.

#### 6. Accidental Release Measures

Evacuate all personnel from affected area. Use appropriate protective equipment. A leak of oxidizing gas mixtures near combustible or flammable materials may present a severe fire or explosion hazard. Eliminate all ignition sources. If leak is in user's equipment, be certain to purge piping with inert gas prior to attempting repairs. If leak is in container or container valve, contact the appropriate emergency telephone number listed in Section 1 or call your closest BOC location.

## 7. Handling and Storage

### **Electrical Classification:**

Nonhazardous.

These mixtures are noncorrosive and may be used with any common structural material.

Use only in well-ventilated areas. Valve protection caps must remain in place unless container is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the system.

Protect cylinders from physical damage. Store in cool, dry, well-ventilated area away from heavily trafficked areas, emergency exits, flammables and combustibles. Do not allow the temperature where cylinders are stored to exceed 125°F (52°C). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in-first out" inventory system to prevent full cylinders being stored for excessive periods of time. Post "NO SMOKING OR OPEN FLAMES" signs in areas where oxidizing mixtures are used or stored. There should be no ignition sources in areas where oxidizers are used or stored.

For additional storage recommendations, consult Compressed Gas Association Pamphlet P-1.

Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, asphyxiation or a toxic exposure.

## 8. Exposure Controls, Personal Protection

### **ENGINEERING CONTROLS:**

Local exhaust to prevent accumulation of high concentrations and maintain air oxygen levels between 19.5 and 23.5%.

### **EYE/FACE PROTECTION:**

Safety goggles or glasses.

### **SKIN PROTECTION:**

Protective gloves made of any suitable material.

### **RESPIRATORY PROTECTION**

Supplies air respirator and escape bottle or self-contained breathing apparatus should be available for emergency use.

### **OTHER/GENERAL PROTECTION:**

Safety shoes.

## 9. Physical and Chemical Properties

PARAMETER	VALUE	UNITS
Physical state (gas, liquid, solid)	: Gas	
Vapor pressure	: Not Available	psia
Vapor density (Ar) at STP (Air = 1)	: 1.38	
Evaporation point	: Not Available	
Boiling point	: Not Available	
Freezing point (Ar)	: -308.9	°F
	: -189.4	°C
PH	: Not Applicable	
Specific gravity	: Not Available	
Oil/water partition coefficient	: Not Available	
Solubility (H <sub>2</sub> O)	: Very slight	
Odor threshold	: Not Applicable	
Odor and appearance	: Odorless, colorless gas	

## 10. Stability and Reactivity

### STABILITY:

Stable

### INCOMPATIBLE MATERIALS:

None known.

### HAZARDOUS DECOMPOSITION PRODUCTS:

None known.

### HAZARDOUS POLYMERIZATION:

Will not occur.

## 11. Toxicological Information

### INHALATION:

Mixtures with less than 19.5% oxygen are inactive biologically and essentially nontoxic. The major hazard is that of oxygen deficiency due to displacement.

Human volunteers which inhaled 90-95% oxygen through a face mask for 6 hours showed signs of tracheal irritation and fatigue. Other symptoms (which might have been caused by placing a tube into the trachea during the experiment) included: sinusitis, conjunctivitis, fever, and symptoms of acute bronchitis.

Poisoning began in dogs 36 hours after inhalation of pure oxygen at atmospheric pressure. Distress was seen within 48 hours and death within 60 hours.

### SKIN AND EYE:

The incompletely developed retinal circulation is more susceptible to toxic levels of oxygen. In premature infants, arterial oxygen tension above 150 mm Hg may cause retrolental fibroplasia. Permanent blindness may occur several months later. One case of severe retinal damage in an adult was reported. An individual suffering from myasthenia gravis developed irreversible retinal atrophy after breathing 80% oxygen for 150 days.

**MSDS:** G-155

**Revised:** 3/22/00

**PRODUCT NAME: OXYGEN IN ARGON (1 PPM TO 50%)**

**REPRODUCTIVE:**

Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

**12. Ecological Information**

No data given.

**13. Disposal Considerations**

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to BOC Gases or authorized distributor for proper disposal.

**14. Transport Information\***

PARAMETER	United States DOT	Canada TDG
PROPER SHIPPING NAME:	Rare gases and oxygen mixtures, compressed/ Compressed gas, oxidizing, n.o.s. (Oxygen, Helium)	Rare Gases and Oxygen Mixtures/ Compressed gas, oxidizing, n.o.s. (Oxygen)
HAZARD CLASS:	2.2	2.2/ 2.2(5.1)
IDENTIFICATION NUMBER:	UN 1980/ UN 3156	UN 1980/ UN 3156
SHIPPING LABEL:	NONFLAMMABLE GAS/ NONFLAMMABLE GAS, OXIDIZER	NONFLAMMABLE GAS/ NONFLAMMABLE GAS, OXIDIZER

\* Transport information is dependent on oxygen concentration. At concentrations greater than 23.5% oxygen, this product is classified as Compressed gases, oxidizing, n.o.s. At oxygen concentrations less than or equal to 23.5%, this product is classified as Rare Gases and Oxygen Mixtures, Compressed.

**15. Regulatory Information**

**SARA TITLE III NOTIFICATIONS AND INFORMATION**

**SARA TITLE III - HAZARD CLASSES:**

Fire Hazard (O<sub>2</sub> > 23.5%)

Sudden Release of Pressure Hazard

**16. Other Information**

ACGIH	American Conference of Governmental Industrial Hygienists
DOT	Department of Transportation
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit
TDG	Transportation of Dangerous Goods
TLV	Threshold Limit Value
WHMIS	Workplace Hazardous Materials Information System

**MSDS: G-155**

**Revised: 3/22/00**

PRODUCT NAME: OXYGEN IN ARGON (1 PPM TO 50%)

Compressed gas cylinders shall not be refilled without the express written permission of the owner. Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).